



Pigtails OM1

Grey 900µm

Funktionen

- OM1 62,5/125 fiber for standard installations
- Halogen-free flame-retardant material (HFFR)
- Various connector options

Anwendung

The 510+ series is designed to meet the standards mainly used in access and transport termination points. Ultra Polished Connectors (UPC) and Angled Polished Connectors (APC) ensures low insertion loss and minimal back reflection. All assemblies are marked with a unique ID-number and all measurement data is stored

Produktinformation

The contact housing made of plastic or metal and the ferrule is made of Zirconia. Each pigtail is equipped with a dust cover and packed in a sealed plastic bag.

The label indicates light attenuation (IL) and reflection (RL) metrics. Can also be supplied in multipacks with 12 or 24 pcs pigtails.

Technische Information

Einfügedämpfung, max [dB]	UPC ≤ 0.2 dB / APC ≤ 0.12 dB
Rückflussdämpfung, min [dB]	UPC ≥ 55 dB / APC ≥ 65 dB

Artikel 7

Artikelbezeichnung	Anzahl der Fasern Aufbau	
Pigtail 1x62,5/125 OM1 SMA Gray 1m 510101	1	SMA
Pigtail 1x62,5/125 OM1 ST/PC Gray 1m 510201	1	ST
Pigtail 1x62,5/125 OM1 ST/PC Grey 1,5m 510201-5	1	–
Pigtail 1x62,5/125 OM1 ST/PC Gray 2m 510202	1	ST
Pigtail 1x62,5/125 OM1 SC/PC Gray 1m 510401	1	SC
Pigtail 1x62,5/125 OM1 SC/PC Gray 2m 510402	1	SC
Pigtail 1x62,5/125 OM1 LC/PC Gray 1m 510L01	1	LC