



# Fiber Measurement assemblies

## MM

**Ruggedized patch cords designed for OTDR network testing**

---

### Features

- 3mm Ruggedized cables
- Choice of connections
- Crush resistant
- Return to base – re-termination service.

## Application

Testing full network links

## Design

Available with most contact configurations SC and LC a variety of standard lengths, consisting of OM1, OM2, OM3 or OM4 fiber. Other configurations may be available upon request.

## Product Information

Each connector is equipped with a dust cover and the cables are packed in a sealed plastic bag. The label indicates the contact values of all contacts for dimming (IL) and reflection (RL).

## Technical Information

<b>Product Color</b>	Black
<b>Fiber Type</b>	OM1;OM2;OM3;OM4
<b>Insertion Loss, max [dB]</b>	≤0,1
<b>Ordering Information</b>	Custom termination available upon request

## Articles 38

Article name	Color	No. of Fibers	Layout	Bend Radius [mm]	Diameter Ø [mm]	Length [m]
Launch cable 1x62,5/125 OM1 FC/PC-FC/PC 2m 5M5502	Black	1	FC-FC	10-25mm	3	2
Launch cable 1x62,5/125 OM1 SC/PC-FC/PC 2m 5M4502	Black	1	SC-FC	10-25mm	3	2
Launch cable 1x62,5/125 OM1 SC/PC-LC/APC 2m 5M4N02	Black	1	SC-LCA	10-25mm	3	2
Launch cable 1x62,5/125 OM1 SC/PC-LC/PC 1m 5M4L01	Black	1	SC-LC	10-25mm	3	1
Launch cable 1x62,5/125 OM1 SC/PC-LC/PC 2m 5M4L02	Black	1	SC-LC	10-25mm	3	2
Launch cable 1x62,5/125 OM1 SC/PC-LC/PC 30m 5M4L30	Black	1	SC-LC	10-25mm	3	30
Launch cable 1x62,5/125 OM1 SC/PC-SC/PC 1m 5M4401	Black	1	SC-SC	10-25mm	3	1
Launch cable 1x62,5/125 OM1 SC/PC-SC/PC 2m 5M4402	Black	1	SC-SC	10-25mm	3	2

Article name	Color	No. of Fibers	Layout	Bend Radius [mm]	Diameter Ø [mm]	Length [m]
Launch cable 1x62,5/125 OM1 SC/PC-SC/PC 30m 5M4430	Black	1	SC-SC	10-25mm	3	30
Launch cable 1x62,5/125 OM1 ST/PC-FC/PC 2m 5M2502	Black	1	ST-FC	10-25mm	3	2
Launch cable 1x62,5/125 OM1 ST/PC-LC/PC 10m 5M2L10	Black	1	ST-LC	10-25mm	3	10
Launch cable 1x62,5/125 OM1 ST/PC-LC/PC 1m 5M2L01	Black	1	ST-LC	10-25mm	3	1
Launch cable 1x62,5/125 OM1 ST/PC-LC/PC 2m 5M2L02	Black	1	ST-LC	10-25mm	3	2
Launch cable 1x62,5/125 OM1 ST/PC-LC/PC 50m 5M2L50	Black	1	ST-LC	10-25mm	3	50
Launch cable 1x62,5/125 OM1 ST/PC-SC/PC 2m 5M2402	Black	1	ST-SC	10-25mm	3	2
Launch cable 1x62,5/125 OM1 ST/PC-SC/PC 30m 5M2430	Black	1	ST-SC	10-25mm	3	30
Launch cable 1x62,5/125 OM1 ST/PC-ST/PC 10m 5M2210	Black	1	ST-ST	10-25mm	3	10
Launch cable 1x62,5/125 OM1 ST/PC-ST/PC 2m 5M2202	Black	1	ST-ST	10-25mm	3	2
Launch cable 1x62,5/125 OM1 ST/PC-ST/PC 30m 5M2230	Black	1	ST-ST	10-25mm	3	30
Launch cable 1x62,5/125 OM1 ST/PC-ST/PC 50m 5M2250	Black	1	ST-ST	10-25mm	3	50
Launch cable 2x62,5/125 OM1 SC/PC-SC/PC 2m 5M4402-D	Black	2	SC-SC	10-25mm	3	2
Mätkablage MM 2x62,5/125 OM1 ST/PC-ST/PC 10m 5M2210-D	-	2	ST-ST	-	-	-
Mätkablage MM 2x62,5/125 OM1 ST/PC-LC/PC 10m 5M2L10-D	-	1	ST-LC	-	-	-
Launch cable 1x50/125 OM2 SC/PC-FC/PC 2m 6M4502	Black	1	SC-FC	10-25mm	3	2
Launch cable 1x50/125 OM2 SC/PC-SC/PC 20m 6M4420	Black	1	SC-SC	10-25mm	3	20
Launch cable 1x50/125 OM2 ST/PC-SC/PC 2m 6M2402	Black	1	ST-SC	10-25mm	3	2
Launch cable 1x50/125 OM2 FC/PC-LC/PC 2m 6M5L02	Black	1	FC-LC	10-25mm	3	2
Launch cable 1x50/125 OM2 SC/PC-LC/PC 2m 6M4L02	Black	1	SC-LC	10-25mm	3	2
Launch cable 1x50/125 OM2 SC/PC-SC/PC 2m 6M4402	Black	1	SC-SC	10-25mm	3	2
Launch cable 1x50/125 OM2 SC/PC-SC/PC 30m 6M4430	Black	1	SC-SC	10-25mm	3	30
Launch cable 1x50/125 OM2 SMA-SC/PC 2m 6M1402	Black	1	SMA-SC	10-25mm	3	2
Launch cable 1x50/125 OM2 ST/PC-LC/PC 10m 6M2L10	Black	1	ST-LC	10-25mm	3	10

Article name	Color	No. of Fibers	Layout	Bend Radius [mm]	Diameter Ø [mm]	Length [m]
Launch cable 1x50/125 OM2 ST/PC-LC/PC 2m 6M2L02	Black	1	ST-LC	10-25mm	3	2
Launch cable 1x50/125 OM2 ST/PC-ST/PC 10m 6M2210	Black	1	ST-ST	10-25mm	3	10
Launch cable 1x50/125 OM2 ST/PC-ST/PC 2m 6M2202	Black	1	ST-ST	10-25mm	3	2
Launch cable 1x50/125 OM4 SC/PC-LC/PC 2m DM4L02	Black	1	SC-LC	10-25mm	3	2
Launch cable 1x50/125 OM4 SC/PC-SC/PC 2m DM4402	Black	1	SC-SC	10-25mm	3	2
Launch cable 2x50/125 OM4 SC/PC-SC/PC 2m DM4402-D	Black	2	SC-SC	10-25mm	3	2