



Pigtails OM4

Purple 900 μ m

Funktionen

- OM4 50/125 fiber for standard installations
- Halogen-free flame-retardant material (HFFR)
- Various connector options

Anwendung

The D10+ series is designed to meet the standards mainly used in access and transport termination points. Polished Connectors (PC) ensures low insertion loss and minimal back reflection. All assemblies are marked with a unique ID-number and all measurement data is stored

Produktinformation

The contact housing made of plastic or metal and the ferrule is made of Zirconia. Each pigtail is equipped with a dust cover and packed in a sealed plastic bag.

The label indicates light attenuation (IL) and reflection (RL) metrics. Can also be supplied in multipacks with 12 or 24 pcs pigtails.

Technische Information

Einfügedämpfung, max [dB] UPC ≤ 0.2 dB / APC ≤ 0.12 dB

Rückflussdämpfung, min [dB] UPC ≥ 55 dB / APC ≥ 65 dB

Artikel 2

| Artikelbezeichnung | Anzahl der Fasern | Aufbau | Durchmesser \varnothing [mm] |
|-----------------------------------------|-------------------|---------|--------------------------------|
| Pigtail 1x50/125 OM4 SC/PC 1m D10401 | 1 | Figtail | 0.9 |
| Pigtail 1x50/125 OM4 LC/PC 1m D10L01 | 1 | Figtail | 0.9 |