



24f Inline Midspan Closure

IP68 24 fibre/splice capacity

Features

- 24 fibre/splice capacity
- Capacity for up to 8 terminated drop cables
- 4 ports and various grommets for multiple cabling solutions
- Midspan storage compartment
- Compact, lightweight and robust design
- Can be installed directly in manholes
- Can be mounted on telegraph poles
- IP68 Rating

Application

The HCFM inline fibre closure is typically used as a branch out splicing point in a fibre access network. Fibres from a distribution cable can be dropped off and spliced onto drop cables or splitters for end-user connections. The closure can also be used as a straight joint for traditional cables or micro cables.

Design

The closure consists of a durable black polymer outer shell with four ports supporting various cable entries, including midspan entry. Internally it is equipped with a 24 fibre splice cassette and the ability to mount up to 4 duplex adaptors. The design allows for easy splicing and re-entry and maintains a 30mm minimum bend radius throughout.

Product Information



Splice capacity 12 (24). Cable diameter Ø3 ~ Ø16
More configurations available upon request

Technical Information

Product Color	Black
IP Rating	IP68
Ordering Information	More configurations available upon request

Articles 2

Article name	Color	No. of Fibers	Layout	Bend Radius [mm]	Impact [J]	Dimensions [mm]	Weight [kg]
24F Inline Closure (Non-Midspan) FCLI-HCF-S024-P00-000-UNL	Black	24	Inline Splice Closure	–	–	240 × 110 × 60	–
24F Inline Midspan Closure FCLI-HCFM-S024-P00-UNL	Black	24	Inline Splice Closure	30mm G652, G657	IK09	240 × 105 × 60mm	