



Safety Compressed Air Hose Assembly

15 Meters rubber grade hose

Features

- Supplied complete with Jaymac safety claw couplings and clamps
- Also comes with Whip Check Hose Safety Device
- Reinforced Rubber

Design

Rubber grade hose intended for general-purpose mobile applications such as small power tools and portable site equipment typically operating at 7 to 16 Bar.

Supplied complete with Jaymac safety claw couplings and clamps, which have fitted as standard anti-vibration nylock style nuts.

Recommended bolt torque setting 23±2 Nm.

Also comes with Whip Check Hose Safety Device

ID mm: 19 ±1

OD mm: 29

Length m: 15

Mass Kg/coil: 11

Working Temp °C: -15 to +70

Hose: Reinforced Rubber

Claw Coupling: Cast Iron QT 400-18

Shore Hardness: Inner: 78A, Outer 67A

Tensile Strength KPa: 5.600

Max Working Pressure Bar: 20

Product Information

SAFE USE INSTRUCTIONS: To be installed and maintained by a competent professional. When selecting a flexible hose, users should take into account the site conditions, including temperatures, oils and pressures to which it will be subjected (HSG39).

WARNING! To avoid whipping hazards, select and use a self-venting socket connector to release downstream pressure before disconnecting this hose. Alternatively, a plug with a controlled venting action, emergency shut-off valve or whip check safety device are additional product selections that can help you prevent uncontrolled whipping of the hose when its inlet end is uncoupled from the socket.

Technical Information

Product Color

Yellow

Articles 1

Article name

15M Extention Air hose - 300psi - C/W Safety coupler and whip cord - claw to claw
FOTT-EXT-HOSE-300PSI-KIT