



# Fiber Optic Jumper Cables for FTTA

Optical Jumper, RDC to LCD RFE

---

## Features

- Robust and secure multifiber connector RDC with IP67 protection
- Enables reduced cabling volume for high density FTTA applications
- Bend insensitive fiber, G657A2
- Branch out to LC duplex connectors protected with plastic cover compatible with FullAXS for Ericsson RRU
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. The assembly is designed to be used in combination with Hybrid cable assembly HRPM 254 110 and HRPM 254 111.

## Technical Information

|                              |   |
|------------------------------|---|
| Lämpötila, käyttö [°C]       | -40 to +85  |
| Lämpötila, asennus [°C]      | -20 to +60  |
| IP-luokitus                  | IP67  |
| Kuidun tyyppi                | G657A2  |
| Liitosvaimennus, max [dB]    | LCD: 0.3, RDC: 0.5  |
| Heijastusvaimennus, min [dB] | 50  |
| Tilastiedot                  | The assembly is delivered in single package in cardboard box. |

## Articles

| Article name   | Pitouis [m] |  |
|--|-------------|--|
| <b>Opto jumper G657A2 RDC(m)-RFE 5M</b><br>HRPM254122/5000 | 5           |  |
| <b>Opto jumper G657A2 RDC(m)-RFE 5M</b><br>HRPM254122/10M  | 10          |  |