



Fiber Optic Jumper Cables for FTTH

Optical Jumper, LCD to LCD

Features

- Robust and secure multifiber connector LC
- Enables reduced cabling volume for high density FTTH applications
- Bend insensitive fiber, G657A2
- Designed for use in RRU with pre-chamber solution to protect the LCD connector
- Quick and easy to install

Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. It is normally used to extend cabling from Multi fiber box NTM504113+.

Technical Information

Lämpötila, käyttö [°C]	-40 to +85
Lämpötila, asennus [°C]	-20 to +60
IP-luokitus	IP67
Kuidun tyyppi	G657A2
Liitosvaimennus, max [dB]	LCD: 0.3, RDC: 0.5
Heijastusvaimennus, min [dB]	50
Tilastiedot	The assembly is delivered in single package in cardboard box.

Articles

Article name	Pituus [m]
Opto jumper G657A2 LCD-LCD 1M HRPM254123/1000	1
Opto jumper G657A2 LCD-LCD 2M HRPM254123/2000	2
Opto jumper G657A2 LCD-LCD 3M HRPM254123/3000	3
Opto jumper G657A2 LCD-LCD 4M HRPM254123/4000	4
Opto jumper G657A2 LCD-LCD 5M HRPM254123/5000	5
Opto jumper G657A2 LCD-LCD 6M HRPM254123/6000	6
Opto jumper G657A2 LCD-LCD 7M HRPM254123/7000	7
Opto jumper G657A2 LCD-LCD 8M HRPM254123/8000	8
Opto jumper G657A2 LCD-LCD 9M HRPM254123/9000	9
Opto jumper G657A2 LCD-LCD 10M HRPM254123/10M	10