



# Fiber Optic Jumper Cables for FTTH

## Optical Jumper, LCD to LCD

---

### Features

- Robust and secure multifiber connector LC
- Enables reduced cabling volume for high density FTTH applications
- Bend insensitive fiber, G657A2
- Designed for use in RRU with pre-chamber solution to protect the LCD connector
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. It is normally used to extend cabling from Multi fiber box NTM504113+.

## Technical Information

<b>Temperature, Operation [°C]</b>	-40 to +85
<b>Temperature, Installation [°C]</b>	-20 to +60
<b>IP Rating</b>	IP67
<b>Fiber Type</b>	G657A2
<b>Insertion Loss, max [dB]</b>	LCD: 0.3, RDC: 0.5
<b>Return Loss, min [dB]</b>	50
<b>Ordering Information</b>	The assembly is delivered in single package in cardboard box.

## Articles

Article name	Weight [kg/km]	Length [m]
<b>Opto jumper G657A2 LCD-LCD 1M</b> HRPM254123/1000	0.08	1
<b>Opto jumper G657A2 LCD-LCD 2M</b> HRPM254123/2000	0.1	2
<b>Opto jumper G657A2 LCD-LCD 3M</b> HRPM254123/3000	0.12	3
<b>Opto jumper G657A2 LCD-LCD 4M</b> HRPM254123/4000	0.14	4
<b>Opto jumper G657A2 LCD-LCD 5M</b> HRPM254123/5000	0.16	5
<b>Opto jumper G657A2 LCD-LCD 6M</b> HRPM254123/6000	0.18	6
<b>Opto jumper G657A2 LCD-LCD 7M</b> HRPM254123/7000	0.2	7
<b>Opto jumper G657A2 LCD-LCD 8M</b> HRPM254123/8000	0.22	8
<b>Opto jumper G657A2 LCD-LCD 9M</b> HRPM254123/9000	0.24	9
<b>Opto jumper G657A2 LCD-LCD 10M</b> HRPM254123/10M	0.26	10