



# Fiber Optic Jumper Cables for FTTH

Optical Jumper, RQC to LCD AOPC

---

## Features

- Robust and secure multifiber connector RDC with IP67 protection
- Enables reduced cabling volume for high density FTTH applications
- Bend insensitive fiber, G657A2
- Branch out to dual 2 fiber cables with LC duplex connectors protected with plastic cover AOPC for Nokia RRU
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. The assembly is designed to be used in combination with Hybrid cable assembly HRPM 254 113 and HRPM 254 114.

## Technical Information

<b>Temperature, Operation [°C]</b>	-40 to +85
<b>Temperature, Installation [°C]</b>	-20 to +60
<b>IP Rating</b>	IP67
<b>Fiber Type</b>	G657A2
<b>Insertion Loss, max [dB]</b>	LCD: 0.3, RDC: 0.5
<b>Return Loss, min [dB]</b>	50
<b>Ordering Information</b>	The assembly is delivered in single package in cardboard box.

## Articles

Article name	Weight (kg/km)	Length (m)	
<b>Opto 4xG657A2 RQcm-2xLCD Nokia 5M</b> HRPM254124/5000	0.16	5	
<b>Opto 4xG657A2 RQcm-2xLCD Nokia 5M</b> HRPM254124/10M	0.16	10	