



# Fiber Optic Jumper Cables for FTTH

Optical Jumper, RQC to LCD

---

## Features

- Robust and secure multifiber connector RDC with IP67 protection
- Enables reduced cabling volume for high density FTTH applications
- Bend insensitive fiber, G657A2
- Branch out to dual LC duplex connectors to support common RRUs
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. The assembly is designed to be used in combination with Hybrid cable assembly HRPM 254 113 and HRPM 254 114.

## Technical Information

<b>Temperature, Operation [°C]</b>	-40 to +85
<b>Temperature, Installation [°C]</b>	-20 to +60
<b>IP Rating</b>	IP67
<b>Fiber Type</b>	G657A2
<b>Insertion Loss, max [dB]</b>	LCD: 0.3, RDC: 0.5
<b>Return Loss, min [dB]</b>	50
<b>Ordering Information</b>	The assembly is delivered in single package in cardboard box.

## Articles

Article name	Weight [kg/km]	Length [m]
<b>Opto 4xG657A2 RQCm-2xLCD Huawei 3M</b> HRPM254125/3000	0.16	3
<b>Opto 4xG657A2 RQCm-2xLCD Huawei 5M</b> HRPM254125/5000	–	5
<b>Opto 4xG657A2 RQCm-2xLCD Huawei 7M</b> HRPM254125/7000	–	7
<b>Opto 4xG657A2 RQCm-2xLCD Huawei 10M</b> HRPM254125/10M	–	10
<b>Opto 4xG657A2 RQCm-2xLCD Huawei 15M</b> HRPM254125/15M	–	15