



Fiber Optic Jumper Cables for FTTA

Optical Jumper, LCD to LCD-RFE

Features

- Robust and secure multifiber connector RDC with IP67 protection
- Enables reduced cabling volume for high density FTTA applications
- Bend insensitive fiber, G657A2
- Branch out to LC duplex connectors protected with plastic cover compatible with FullAXS for Ericsson RRU
- Quick and easy to install

Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. It is normally used to extend cabling from Multi fiber box NTM504113+.

Technical Information

Temperature, Operation [°C]	-40 to +85
Temperature, Installation [°C]	-20 to +60
IP Rating	IP67
Fiber Type	G657A2
Insertion Loss, max [dB]	LCD: 0.3, RDC: 0.5
Return Loss, min [dB]	50
Ordering Information	The assembly is delivered in single package in cardboard box.

Articles

Article name	Length [m]
Opto jumper G657A2 LCD-RFE 2m HRPM254127/2000	2
Opto jumper G657A2 LCD-RFE 3m HRPM254127/3000	3
Opto jumper G657A2 LCD-RFE 5m HRPM254127/5000	5
Opto jumper G657A2 LCD-RFE 10m HRPM254127/10M	10