



# Fiber Optic Jumper Cables for FTTA

Optical Jumper, LCD to LCD-RFE

---

## Features

- Robust and secure multifiber connector RDC with IP67 protection
- Enables reduced cabling volume for high density FTTA applications
- Bend insensitive fiber, G657A2
- Branch out to LC duplex connectors protected with plastic cover compatible with FullAXS for Ericsson RRU
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. It is normally used to extend cabling from Multi fiber box NTM504113+.

## Technical Information

Lämpötila, käyttö [°C]	-40 to +85
Lämpötila, asennus [°C]	-20 to +60
IP-luokitus	IP67
Kuidun tyyppi	G657A2
Liitosvaimennus, max [dB]	LCD: 0.3, RDC: 0.5
Heijastusvaimennus, min [dB]	50
Tilastiedot	The assembly is delivered in single package in cardboard box.

## Articles

Article name	Pituus [m]	
Opto jumper G657A2 LCD-RFE 2m HRPM254127/2000	2	
Opto jumper G657A2 LCD-RFE 3m HRPM254127/3000	3	
Opto jumper G657A2 LCD-RFE 5m HRPM254127/5000	5	
Opto jumper G657A2 LCD-RFE 10m HRPM254127/10M	10	