



# Fiber Optic Jumper Cables for FTTH

Optical Jumper, LCD to LCD AOPC

---

## Features

- Robust and secure multifiber connectors with IP67 protection
- Enables reduced cabling volume for high density FTTH applications
- Bend insensitive fiber, G657A2
- Branch out to 2 fiber cables with LC duplex connectors protected with plastic cover AOPC for Nokia RRU
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. It is normally used to extend cabling from Multi fiber box NTM504113+.

## Technical Information

<b>Temperature, Operation [°C]</b>	-40 to +85
<b>Temperature, Installation [°C]</b>	-20 to +60
<b>IP Rating</b>	IP67
<b>Fiber Type</b>	G657A2
<b>Insertion Loss, max [dB]</b>	LCD: 0.3, RDC: 0.5
<b>Return Loss, min [dB]</b>	50
<b>Ordering Information</b>	The assembly is delivered in single package in cardboard box.

## Articles 4

Article name	Length [m]
<b>Opto jumper G657A2 LCD-AOPC Nokia 2m</b> HRPM254128/2000	2
<b>Opto jumper G657A2 LCD-AOPC Nokia 3m</b> HRPM254128/3000	3
<b>Opto jumper G657A2 LCD-AOPC Nokia 5m</b> HRPM254128/5000	5
<b>Opto jumper G657A2 LCD-AOPC Nokia 10m</b> HRPM254128/10M	10