



# Fiber Optic Jumper Cables for FTTH

## Optical Jumper, RDC to LCD AOPC

---

### Features

- Robust and secure multifiber connector RDC with IP67 protection
- Enables reduced cabling volume for high density FTTH applications
- Bend insensitive fiber, G657A2
- Branch out to 2 fiber cables with LC duplex connectors protected with plastic cover AOPC for Nokia RRU
- Quick and easy to install

## Application

The assembly is designed for interconnection between transmission equipment and tower mounted Radio Units. The assembly is designed to be used in combination with Hybrid cable assembly HRPM 254 110 and HRPM 254 111.

## Technical Information

<b>Lämpötila, käyttö [°C]</b>	-40 to +85
<b>Lämpötila, asennus [°C]</b>	-20 to +60
<b>IP-luokitus</b>	IP67
<b>Kuidun tyyppi</b>	G657A2
<b>Liitosvaimennus, max [dB]</b>	LCD: 0.3, RDC: 0.5
<b>Heijastusvaimennus, min [dB]</b>	50
<b>Tilautiedot</b>	The assembly is delivered in single package in cardboard box.

## Articles 2

Article name	Väri	Pituus [m]
<b>Opto jumper G657A2 RDC(m)-AOPC 5M</b> HRPM254129/5000	Black	5
<b>Opto jumper G657A2 RDC(m)-AOPC 10M</b> HRPM254129/10M	Black	5