

High Performance Air Blown Fiber – Multimode

ABF 2-12 fibers OM3, OM4 S12 - Box

Features

- Extra strong and durable design
- Smooth, low-friction sheath
- 2, 4, 6, 8 or 12 fiber, Multimode OM3 and OM4 bend resistant fibers
- Extra wide operational temperature range
- Water and Ice tested
- State of the art blowing performance
- Zero sheath shrinkage

Application

Hexatronic Stingray is a high performance Air Blown Fiber Unit intended for blowing into microducts. The main application area is for fiber access networks such as Fiber To The Home (FTTH), campus networks and data centers.


Design

The Hexatronic Stingray Air Blown Fiber is designed with durability and performance in mind. The unique design offers a combination of properties previously not available on the market. A sturdy fiber unit with state of the art fiber blowing performance increases the installation success rate and provides quick and problem free installation. The Stingray has a unique sheath material with zero sheath shrinkage ,wich means no fragile splice points or sensitive installations in wall outlets or fiber cabinets.

The Air Blown Fiber unit is colored dark blue for good visibility when installed in semi-translucent microducts.

The Air Blown Fiber is delivered in bulk lengths in cardboard PANs. For optimum blowing performance, use the Hexatronic Air Blown Tool LTT 179 2040.

Product Information



- 1 Primary coated fiber: Silica, acrylate
- 2 Primary coating: UV-cured acrylate
- 3 Sheath: Low friction polyolefin

A mechanical filler is used in the 2-fiber unit as well as in the center of the 6-fiber unit.

Technical Information

Tuotteen väri	Dark blue
Värijärjestys	S12
Lämpötila, käyttö [°C]	-25 to +70
Lämpötila, varastointi [°C]	-45 to +70
Lämpötila, asennus [°C]	-15 to +60
Kuidun tyyppi	OM3;OM4
Vaimennus @Aallonpituudella [nm]	850/1310
Max. vaimennus [dB/km]	3.0/1.0
Vaatimustenmukaisuus	Air blown fiber: IEC 60794-5-20
Asennustiedot	<p>Typical installation performance:</p> <ul style="list-style-type: none"> ▪ Ducts ID 3.5-4 mm: 1000 m <p>Installation performance is affected by the installed path, environmental conditions, installation equipment etc and actual performance may therefore deviate from the above specified values.</p>
Tilustiedot	<p>Supplied lengths: 1000, 2000, 4000, 6000 m</p> <p>Delivered in cardboard boxes</p>

Technical Details

S12 Fiber och rör Fibers and tubes	1	2	3	4	5	6	7	8	9	10	11	12
	Röd Red	Blå Blue	Vit White	Grön Green	Gul Yellow	Grå Grey	Brun Brown	Svart Black	Violett Violet	Orange	Turkos Turquoise	Rosa Pink
	13	14	15	16	17	18	19	20	21	22	23	24
	Röd Red	Blå Blue	Vit White	Grön Green	Gul Yellow	Grå Grey	Brun Brown	Klar Clear	Violett Violet	Orange	Turkos Turquoise	Rosa Pink

Articles 9

Article name	Väri	Kuitujen lkm	Asettelu	Vetolujuus, asennettaessa [N]	Halkaisija Ø [mm]	Paino [kg/km]	Pituus [m]	Toimitustapa
AEF 12 MM 50 OM3 PAN Stingray KRPM258023/1000M	Dark blue	12	1x12	30	1.4	1.65	1000	Box
AEF 12 MM 50 OM3 PAN Stingray KRPM258023/2000M	Dark blue	12	1x12	30	1.4	1.65	2000	Box
AEF 12 MM 50 OM3 PAN Stingray KRPM258023/4000M	Dark blue	12	1x12	30	1.4	1.65	4000	Box
AEF 4 MM 50 OM3 PAN Stingray KRPM258024/2000M	Dark blue	4	1x4	10	1.1	1.02	2000	Box
AEF 2 MM 50 OM3 PAN Stingray KRPM258025/2000M	Dark blue	2	1x2	5	1.1	0.94	2000	Box
AEF 12 MM 50 OM4 PAN Stingray KRPM258030/1000M	Dark blue	12	1x12	30	1.4	1.65	1000	Box
AEF 12 MM 50 OM4 PAN Stingray KRPM258030/2000M	Dark blue	12	1x12	30	1.4	1.65	2000	Box
AEF 12 MM 50 OM4 PAN Stingray KRPM258030/4000M	Dark blue	12	1x12	30	1.4	1.65	4000	Box
AEF 4 MM 50 OM4 PAN Stingray KRPM258032/4000M	Dark blue	4	1x4	10	1.1	1.02	4000	Box