



High Performance Air Blown Fiber – Pre-terminated

ABF 2-12 fibers G657A2 TIA598 - Reel

Features

- Pre-terminated fiber on reel
- Time saving installation
- Several connector options
- Extra strong and durable design
- Smooth, low-friction sheath
- 2 or 4 fibers, G657A2 bend resistant fibers
- Extra wide operational temperature range
- Water and Ice tested
- State of the art blowing performance
- Zero sheath shrinkage

Application

Hexatronic Stingray is a high performance Air Blown Fiber Unit intended for blowing into microducts. The main application area is for fiber access networks such as Fiber To The Home (FTTH).


Design

The Hexatronic Stingray Air Blown Fiber is designed with durability and performance in mind. The unique design offers a combination of properties previously not available on the market. A sturdy fiber unit with state of the art fiber blowing performance increases the installation success rate and provides quick and problem free installation. The Stingray has a unique sheath material with zero sheath shrinkage ,wich means no fragile splice points or sensitive installations in wall outlets or fiber cabinets.

The Air Blown Fiber unit is colored dark blue for good visibility when installed in semi-translucent microducts.

The Air Blown Fiber is delivered in bulk lengths in cardboard PANs. For optimum blowing performance, use the Hexatronic Air Blown Tool LTT 179 2040.

Product Information



- 1 Primary coated fiber: Silica, acrylate
- 2 Primary coating: UV-cured acrylate
- 3 Sheath: Low friction polyolefin

A mechanical filler is used in the 2-fiber unit as well as in the center of the 6-fiber unit.

Technical Information

Product Color	Dark blue
Color Code	TIA598
Temperature, Operation [°C]	-40 to +70
Temperature, Storage [°C]	-40 to +70
Temperature, Installation [°C]	-15 to +50
Fiber Type	G657A2
Attenuation @Wavelength [nm]	1310/1550
Maximum Attenuation [dB/km]	0.38/0.25
Insertion Loss, max [dB]	0.25
Return Loss, min [dB]	SC/UPC & LC/UPC: 55, SC/APC & LC/APC: 65
Conformance	<p>Air blown fiber: IEC 60794-5-20</p> <p>Bend radius: IEC 60794-1-21, Method E11</p> <p>Crush resistance: IEC 60794-1-21 Method E3</p> <p>Kink: IEC 60794-1-21 Method E10</p> <p>Tensile force during installation: IEC 60794-1-22, Method F1</p> <p>Fiber parameters and tests according to the IEC series 60793-2 and 60793-1</p>
Technical Notes	<p>Water immersion and repeated freeze test:</p> <p>Hexatronic standard test, 100 cycles, -25, to +15°C</p>
Installation Notes	<p>Typical installation performance:</p> <ul style="list-style-type: none"> • Ducts ID 3.5-4 mm: 1000 m <p>Installation performance is affected by the installed path, environmental conditions, installation equipment etc and actual performance may therefore deviate from the above specified value</p>
Ordering Information	<p>Supplied lengths: Fixed lengths from 30 to 1000 m</p> <p>Delivered on miniature cardboard reels</p>

Technical Details

TIA-598 Fibers and Tubes	1	2	3	4	5	6	7	8	9	10	11	12
	Blue	Orange	Green	Brown	Slate	White	Red	Black	Yellow	Violet	Rose	Aqua
	13	14	15	16	17	18	19	20	21	22	23	24
	Blue	Orange	Green	Brown	Slate	White	Red	Clear	Yellow	Violet	Rose	Aqua

TIA 598 Color Code Chart

Articles

Article name	Color	No. of Fibers	Bend Radius [mm]	Tensile Force, Installation [N]	Diameter Ø [mm]	Length [m]	Form of Delivery
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/30M	Dark blue	2	20	5	1.1	30	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/50M	Dark blue	2	20	5	1.1	50	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/70M	Dark blue	2	20	5	1.1	70	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/100M	Dark blue	2	20	5	1.1	100	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/150M	Dark blue	2	20	5	1.1	150	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/200M	Dark blue	2	20	5	1.1	200	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/250M	Dark blue	2	20	5	1.1	250	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/300M	Dark blue	2	20	5	1.1	300	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/350M	Dark blue	2	20	5	1.1	350	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/400M	Dark blue	2	20	5	1.1	400	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/450M	Dark blue	2	20	5	1.1	450	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/500M	Dark blue	2	20	5	1.1	500	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/550M	Dark blue	2	20	5	1.1	550	Reel

Article name	Color	No. of Fibers	Bend Radius [mm]	Tensile Force, Installation [N]	Diameter Ø [mm]	Length [m]	Form of Delivery
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/600M	Dark blue	2	20	5	1.1	600	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/650M	Dark blue	2	20	5	1.1	650	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/700M	Dark blue	2	20	5	1.1	700	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/750M	Dark blue	2	20	5	1.1	750	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/800M	Dark blue	2	20	5	1.1	800	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/850M	Dark blue	2	20	5	1.1	850	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/900M	Dark blue	2	20	5	1.1	900	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/950M	Dark blue	2	20	5	1.1	950	Reel
ABF 2LC/APC 2G657A2 TIA598 REEL S KRPM258018/1000M	Dark blue	2	20	5	1.1	1000	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/30M	Dark blue	4	20	10	1.1	30	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/50M	Dark blue	4	20	10	1.1	50	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/70M	Dark blue	4	20	10	1.1	70	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/100M	Dark blue	4	20	10	1.1	100	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/150M	Dark blue	4	20	10	1.1	150	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/200M	Dark blue	4	20	10	1.1	200	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/250M	Dark blue	4	20	10	1.1	250	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/300M	Dark blue	4	20	10	1.1	300	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/350M	Dark blue	4	20	10	1.1	350	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/400M	Dark blue	4	20	10	1.1	400	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/500M	Dark blue	4	20	10	1.1	500	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/600M	Dark blue	4	20	10	1.1	600	Reel

Article name	Color	No. of Fibers	Bend Radius [mm]	Tensile Force, Installation [N]	Diameter Ø [mm]	Length [m]	Form of Delivery
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/700M	Dark blue	4	20	10	1.1	700	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/800M	Dark blue	4	20	10	1.1	800	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/900M	Dark blue	4	20	10	1.1	900	Reel
ABF 2LC/APC 4G657A2 TIA598 REEL S KRPM258021/1000M	Dark blue	4	20	10	1.1	1000	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/30M	Dark blue	2	20	5	1.1	30	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/50M	Dark blue	2	20	5	1.1	50	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/70M	Dark blue	2	20	5	1.1	70	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/100M	Dark blue	2	20	5	1.1	100	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/150M	Dark blue	2	20	5	1.1	150	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/200M	Dark blue	2	20	5	1.1	200	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/250M	Dark blue	2	20	5	1.1	250	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/300M	Dark blue	2	20	5	1.1	300	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/350M	Dark blue	2	20	5	1.1	350	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/400M	Dark blue	2	20	5	1.1	400	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/500M	Dark blue	2	20	5	1.1	500	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/600M	Dark blue	2	20	5	1.1	600	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/700M	Dark blue	2	20	5	1.1	700	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/800M	Dark blue	2	20	5	1.1	800	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/900M	Dark blue	2	20	5	1.1	900	Reel
ABF 2SC/APC 2G657A2 TIA598 REEL S KRPM258026/1000M	Dark blue	2	20	5	1.1	1000	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/30M	Dark blue	4	20	10	1.1	30	Reel

Article name	Color	No. of Fibers	Bend Radius [mm]	Tensile Force, Installation [N]	Diameter Ø [mm]	Length [m]	Form of Delivery
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/50M	Dark blue	4	20	10	1.1	50	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/70M	Dark blue	4	20	10	1.1	70	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/100M	Dark blue	4	20	10	1.1	100	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/150M	Dark blue	4	20	10	1.1	150	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/200M	Dark blue	4	20	10	1.1	200	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/250M	Dark blue	4	20	10	1.1	250	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/300M	Dark blue	4	20	10	1.1	300	Reel
ABF 4SC/APC 4G657A2 TIA598 REEL S KRPM258027/500M	Dark blue	4	20	10	1.1	500	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/30M	Dark blue	2	20	5	1.1	30	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/50M	Dark blue	2	20	5	1.1	50	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/70M	Dark blue	2	20	5	1.1	70	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/100M	Dark blue	2	20	5	1.1	100	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/150M	Dark blue	2	20	5	1.1	150	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/200M	Dark blue	2	20	5	1.1	200	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/250M	Dark blue	2	20	5	1.1	250	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/300M	Dark blue	2	20	5	1.1	300	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/350M	Dark blue	2	20	5	1.1	350	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/400M	Dark blue	2	20	5	1.1	400	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/450M	Dark blue	2	20	5	1.1	450	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/500M	Dark blue	2	20	5	1.1	500	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/550M	Dark blue	2	20	5	1.1	550	Reel

Article name	Color	No. of Fibers	Bend Radius [mm]	Tensile Force, Installation [N]	Diameter Ø [mm]	Length [m]	Form of Delivery
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/600M	Dark blue	2	20	5	1.1	600	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/650M	Dark blue	2	20	5	1.1	650	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/700M	Dark blue	2	20	5	1.1	700	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/750M	Dark blue	2	20	5	1.1	750	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/800M	Dark blue	2	20	5	1.1	800	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/850M	Dark blue	2	20	5	1.1	850	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/900M	Dark blue	2	20	5	1.1	900	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/950M	Dark blue	2	20	5	1.1	950	Reel
ABF 1SC/APC 2G657A2 TIA598 REEL S KRPM258029/1000M	Dark blue	2	20	5	1.1	1000	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/1000M	Dark blue	2	20	5	1.1	1000	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/30M	Dark blue	2	20	5	1.1	30	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/50M	Dark blue	2	20	5	1.1	50	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/70M	Dark blue	2	20	5	1.1	70	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/100M	Dark blue	2	20	5	1.1	100	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/150M	Dark blue	2	20	5	1.1	150	Reel
ABF 1SC/APC 2G657A2 TIA598 Reel RPM258029/200M	Dark blue	2	20	5	1.1	200	Reel
ABF 1SC/APC 2G657A2 TIA598 Reel RPM258029/250M	Dark blue	2	20	5	1.1	250	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/300M	Dark blue	2	20	5	1.1	300	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/350M	Dark blue	2	20	5	1.1	350	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/400M	Dark blue	2	20	5	1.1	400	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/450M	Dark blue	2	20	5	1.1	450	Reel

Article name	Color	No. of Fibers	Bend Radius [mm]	Tensile Force, Installation [N]	Diameter Ø [mm]	Length [m]	Form of Delivery
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/500M	Dark blue	2	20	5	1.1	500	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/550M	Dark blue	2	20	5	1.1	550	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/600M	Dark blue	2	20	5	1.1	600	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/650M	Dark blue	2	20	5	1.1	650	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/700M	Dark blue	2	20	5	1.1	700	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/750M	Dark blue	2	20	5	1.1	750	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/800M	Dark blue	2	20	5	1.1	800	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/850M	Dark blue	2	20	5	1.1	850	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/900M	Dark blue	2	20	5	1.1	900	Reel
ABF 1SC/APC 2G657A2 TIA-598 Reel RPM258029/950M	Dark blue	2	20	5	1.1	950	Reel