



# LightMate Stackable Patch Splice Panel LC and SC

ODF complete with interior for fiber splicing (heatshrink)

---

## Features

- Could be installed individual or stacked together
- Duplex SC or LC QUAD versions
- Up to 48 SC connections (1U)
- Up to 96 LC connections (1U)
- Sliding drawer allows internal access, even when it's stacked
- Heatshrink Splice holders for single and ribbon fiber
- Removable blind-plate to access additional ODF
- Brackets to connect additional ODF is sold as accessorie
- Suitable for cable dimensions <28mm
- Guiding for fibers and holders for fan out sleeves

## Application

- Optical Networks
- CATV Networks
- Enterprise
- Data Networks
- Customer Premise Deployment
- FTTx

## Design

- Adjustable depth in racks
- Sheet metal with stainless steel front
- Coral white powder coating

## Product Information

- No limitations to build number of ODFs in height, only total weight limits what a person can lift.

## Technical Information

<b>Product Color</b>	Coral white
<b>Fiber Type</b>	G657A1;G652D;G657A2;OM1;OM2;OM3;OM4;OM5
<b>Conformance</b>	REACH and ROHS compliant
<b>Ordering Information</b>	Can be ordered complete with pigtailed, adapters and pre-terminated cable Labeling kit LM-5936/90 included in each ODF 1-288 SC and 1-384 LC. Additional labeling kit available

## Articles 3

Article name	Color	No. of Fibers	Layout	Dimensions [mm]	Weight [kg]	Form of Delivery
<b>LightMate ODF 1U, stackable</b> LM-5936/101	Coral white	96	SCD or LCQ	485 × 255 × 44	3,86	Box
<b>Stackable ODF, label kit</b> LM-5936/90	Silver	–	kaStackabl- ODFFStackabl	366 × 50 × 1	0.12	10pcs
<b>Stackable ODF, 2U bracket (pair)</b> LM-5936/92	Coral white	–	StackableODF, 2U bracket (p- UackeODF, 2U bracket (p	118 × 88 × 28	0,220	Pair