



LightMate Stackable Patch Splice Panel LC and SC

ODF complete with interior for fiber splicing (heatshrink)

Features

- Could be installed individual or stacked together
- Duplex SC or LC QUAD versions
- Up to 48 SC connections (1U)
- Up to 96 LC connections (1U)
- Sliding drawer allows internal access, even when it's stacked
- Heatshrink Splice holders for single and ribbon fiber
- Removable blind-plate to access additional ODF
- Brackets to connect additional ODF is sold as accessories
- Suitable for cable dimensions <28mm
- Guiding for fibers and holders for fan out sleeves

Application

- Optical Networks
- CATV Networks
- Enterprise
- Data Networks
- Customer Premise Deployment
- FTTx

Product Information

- No limitations to build number of ODFs in height, only total weight limits what a person can lift.

Technical Information

Kuidun tyyppi

G657A1;G652D;G657A2;OM1;OM2;OM3;OM4;OM5

Articles 3

Article name	Kuitujen lkm	Asettelu
LightMate ODF 1U, stackable LM-5936/101	96	SCD or LCQ
Stackable ODF, label kit LM-5936/90	–	kaStackabl- ODFFStackabl
Stackable ODF, 2U bracket (pair) LM-5936/92	–	StackableODF, 2U bracket (p- UackeODF, 2U bracket (p