

Microduct Assembly 5/3.5 mm Indoor – High Grade

FRD 5/3.5 mm 1-24 -way HG

Features

- For indoor installation
- 5/3.5 mm microducts
- Halogen-free, flame-retardant, high grade
- 1, 4, 7, 12, 19 or 24 over-sheathed ducts
- Low friction inner surface for maximum installation lengths


Application

The indoor tight protected duct assemblies consist of a number of microducts with an inner low friction, antistatic surface that enables installation of air-blown fibers. These microducts are highly flame retardant and therefore suitable for indoor use.

Design

The duct assemblies are available in several versions from 1 to 24 microducts. Each microduct has an outer/inner diameter of 5/3.5 mm. The microducts and duct assemblies including the outer sheath are made of halogen-free, flame-retardant polymer. One unsheathed single duct version for minimal cross section is available for installation in existing external protective microducts or sheaths.

Product Information



Microducts and sheath: Halogen-free, flame-retardant polyolefin

Technical Information

Temperature, Operation [°C]	-20 to +60
Temperature, Storage [°C]	-20 to +60
Temperature, Installation [°C]	-20 to +50
Reaction to Fire	IEC60332-3-24, IEC60332-1

Conformance

- Abrasion:** IEC 60794-1-2-E2B(1)
- Kink:** IEC 60794-1-2-E10, 20 x outer diameter
- Impact:** IEC 60794-1-2-E4
- Crush:** IEC 60794-1-2-E3
- Tensile:** IEC 60794-1-2-E
- Bend:** IEC 60794-1-2-E11A
- Torsion:** IEC 60794-1-2-E
- Flexibility:** IEC 60794-1-2-E8
- Inner Clearance:** IEC 60794-5-20, IEC 60794-5-10, Ann. D
- Flammability:** IEC60332-3-24, IEC60332-1
- Smoke density:** .IEC61034-2
- Smoke volume:** ASTM E662
- Halogen Content:** IEC 60754-1, 0%
- Acidity/Halogen contents:** IEC60754-1/-2
- Toxicity index:** DEFSTAN 02-713

Marking

Duct assemblies have markings showing the tube length.
The individual microducts are numbered.

Installation Notes

Flammability according to IEC60332-3-24 refers to sheathed empty ducts and sheathed ducts installed with typical versions of Hexatronic blown fiber units. 1-way unsheathed duct MPB30246/01 excluded. The unsheathed duct shall be installed in flame resistant protective cover for best fire performance.

Articles 19

Article name	EL-No.	Color	Layout	Bend Radius [mm]	Tensile Force, Installation [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]	Length [m]
Microduct 5/3.5 ID HGrade MPB30202/1	2804129	White	5/3.5	50	60	450	2	5	15	500/PLAST
Microduct 5/3.5 ID HGrade 100 m PAN MPB30202/1-10		White	5/3.5	50	60	450	2	5	15	100/PAN
Microduct 5/3.5 ID HGrade 500 m MPB30202/1-2		White	5/3.5	50	60	450	2	5	15	500/PLAST
Microduct 1x5/3.5 ID HGrade MPB30201/1	2804128	White	1x5/3.5	72	110	450	2	7.2	48	1000/K5, 2000/K6, 500/K4
Microduct 1x5/3.5 ID HGrade 500 m MPB30201/1-2		White	1x5/3.5	72	110	450	2	7.2	48	500/K4

Article name	EL-No.	Color	Layout	Bend Radius [mm]	Tensile Force [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]	Length [m]
Microduct 2x5/3.5 IDHGrade MPB30203/2		White	2x5/3.5	150	300	900	2	7.2 × 12.2	80	2000/K10, 1000/K7, 500/K6
Microduct 2x5/3.5 IDHGrade 500 m MPB30203/2-2		White	2x5/3.5	150	300	900	2	7.2 × 12.2	80	500/K6
Microduct 4x5/3.5 IDHGrade MPB30203/4		White	4x5/3.5	150	400	1500	5	12.2 × 12.2	130	1000/K9, 500/K9, 4000/K14, 2000/K10
Microduct 4x5/3.5 IDHGrade 500 m MPB30203/4-2		White	4x5/3.5	150	400	1500	5	12.2 × 12.2	135	500/K6
Microduct 7x5/3.5 IDHGrade MPB30204/7CX		White	7x5/3.5	220	600	1500	10	17.2	198	4000/K20, 2000/K14, 1000/K11, 500/K11
Microduct 7x5/3.5 IDHGrade MPB30204/7		White	7x5/3.5	220	600	1500	10	17.2	198	4000/K20, 2000/K14, 1000/K11, 500/K11
Microduct 7x5/3.5 IDHGrade 500 m MPB30204/7-2		White	7x5/3.5	220	600	1500	10	17.2	190	500/K9
Microduct 12x5/3.5 IDHGrade MPB30205/12CX		White	12x5/3.5	300	950	1500	10	22.9	305	4000/K22, 2000/K16, 1000/K12, 500/K11
Microduct 12x5/3.5 IDHGrade MPB30205/12		White	12x5/3.5	300	950	1500	10	22.9	305	4000/K22, 2000/K16, 1000/K12, 500/K11
Microduct 12x5/3.5 IDHGrade 500 m MPB30205/12-2		White	12x5/3.5	300	950	1500	10	22.9	305	500/K10
Microduct 19x5/3.5 IDHGrade MPB30206/19CX		White	19x5/3.5	350	1300	1500	10	26.9	437	1000/K14, 3000/K24, 2000/K20, 4000/K24, 500/K12
Microduct 19x5/3.5 IDHGrade MPB30206/19		White	19x5/3.5	350	1300	1500	10	26.9	437	1000/K14, 3000/K24, 2000/K20, 4000/K24, 500/K12
Microduct 1x10/8+24x5/3.5 IDHGrade MPB30207/24CX		White	1x10/ 8+24x5/ 3.5	500	1800	4000	10	32.5	462	4000/K24, 2000/K22, 500/K14, 1000/K18
Microduct 1x10/8+24x5/3.5 IDHGrade MPB30207/24		White	1x10/ 8+24x5/ 3.5	500	1800	4000	10	32.5	462	4000/K24, 2000/K22, 500/K14, 1000/K18