

# Underwater Microduct 12/10-20/16 mm

**UWD 12/10-20/16 mm 1-3 -way**

---

## Features

- For underwater installation
- Water depth down to 50 m
- Compact design, down to 22.5 mm in diameter
- Microduct OD/ID: 12/10 mm or 20/16 mm options
- Steel wire reinforcement - Water blocking Al-foil


## Application

The underwater microduct is a single armored duct for shallow submarine installations. It is designed to be used with micro cables and can easily be connected to land based microducts with microduct connectors or adapters. The microduct is suitable for lakes and river crossings in all types of fiber access networks.

## Design

This underwater microduct is based on a 12/10 or 20/16 mm PE microduct protected by an aluminum foil and a polyethylene sheath. Outside the sheath there is a layer of galvanized steel wires covered with a heavy-duty layer of HDPE polymer. The steel wire reinforcement provides reliable mechanical protection, enabling installation and operation during rough conditions.

## Product Information



- 1 Microduct: Polyethylene
- 2 Wrapping: Plastic Al-foil
- 3 Sheath: Polyethylene, black
- 4 Armoring: Galvanized steel wires
- 5 Sheath: Polyethylene, black

## Technical Information

<b>Temperature, Operation [°C]</b>	-30 to +60
<b>Temperature, Storage [°C]</b>	-40 to +70
<b>Temperature, Installation [°C]</b>	-15 to +40

**Technical Notes**

Tensile force 12/10 -

Permanent: 10 kN

During installation: 15 kN

Tensile force 20/16 -

Permanent: 20 kN

During installation: 30 kN

**Ordering Information**

Max continuous length: 2 km

**Articles 4**

Article name	EL-No.	Color	Layout	Bend Radius [mm]	Tensile Force [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]	Weight in Water [kg/km]	Length [m]
<b>Armoured Underwater 1x20/16 Duct</b> MPB30217/026	2800876	Black	1x20/16	400	30000	4500	60	30.5	1400	650	1000/K18, 2000/K22
<b>Armoured UnderWater 1x12/10 Duct</b> MPB30217/020	2800121	Black	1x12/10	400	15000	2500	10	22.5	800	—	2000/K18
<b>Armoured 3x12/10 duct</b> MPB30217/024		Black	3x12/10	800	40000	—	—	39.5	2516	—	2000/K26
<b>Armoured 40/32 duct</b> MPB30217/022		Black	40/32	400	—	—	—	40	4949	—	275/K22, 750/K26, 1710/K30