



Microduct Assembly 5/3.5-12/10 mm Aerial

TPD 5/3.5-12/10 mm TIA598

Features

- Aerial, dielectric, self supporting design
- 5/3.5, 10/8 or 12/10 mm microduct system
- Low friction inner surface for maximum installation lengths
- Excellent UV resistance
- Slim, lightweight design with low visual impact

Application

The tight protected duct assemblies consist of a number of microducts with an inner low friction surface that enables air blown installation of air blown fibers or micro cables.

The duct assemblies are dielectric and self supported. This makes the ducts suitable for aerial applications along power lines.

Design

The duct assemblies are available in several configurations with 5/3.5, 10/8 and 12/10 mm microducts (OD/ID) for the installation of customer drop installations with air blown fiber and distribution micro cables into the same infrastructure.

Depending on type, the assemblies are of All-Dielectric Self-Supporting (ADSS) or Figure-8 design. The available configurations are chosen for perfect match with Hexatronic aerial blown fiber system for fiber access networks.

Product Information

Microducts: HDPE

Strain relief: FRP or aramide yarn

Technical Information

Color Code	TIA598
Temperature, Operation [°C]	-40 to +60
Temperature, Storage [°C]	-40 to +60
Temperature, Installation [°C]	-15 to +50
Conformance	<p>Abrasion: IEC 60794-1-2-E2B(1)</p> <p>Kink: IEC 60794-1-2-E10, 20 x outer diameter</p> <p>Impact: IEC 60794-1-2-E4</p> <p>Crush: IEC 60794-1-2-E3</p> <p>Tensile: IEC 60794-1-2-E</p> <p>Bend: IEC 60794-1-2-E11A</p> <p>Torsion: IEC 60794-1-2-E</p> <p>Flexibility: IEC 60794-1-2-E8</p> <p>Inner Clearance: IEC 60794-5-20, IEC 60794-5-10, Ann. D</p>
Marking	<p>Duct assemblies have markings showing the tube length.</p> <p>The individual microducts are identified by their color and position in the bundle.</p>

Technical Details

TIA-598 Microducts 1-24	1	2	3	4	5	6	7	8	9	10	11	12
	Blue	Orange	Green	Brown	Slate	White	Red	Black	Yellow	Violet	Rose	Aqua
	Blue 1	Orange 1	Green 1	Brown 1	Slate 1	White 1	Red 1	Black 1	Yellow 1	Violet 1	Rose 1	Aqua 1
	Blue 2	Orange 2	Green 2	Brown 2	Slate 2	White 2	Red 2	Black 2	Yellow 2	Violet 2	Rose 2	Aqua 2
	13	14	15	16	17	18	19	20	21	22	23	24

Articles 12

Article name	Color	Layout	Bend Radius [mm]	Tensile Force, Installation [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]	Length [m]
Aerial 1x5/3.5 TIA MPB30222/1B	Black	1x5/3.5	100	1000	500	3	8	40	1000/K6, 500/K5
Aerial 1x5/3.5 Fig8 TIA MPB30224/1B	Black	1x5/3.5	–	–	500	3	15.5 × 7.1	80	2000/K10, 1000/K9, 500/K9
Aerial 4x5/3.5 Fig8 TIA MPB30224/4B	Black	4x5/3.5	200	1000	500	3	24 × 12	122	500/K12, 1000/K12, 2000/K14
Aerial 19x5/3.5 Fig8 TIA598 MPB30224/19B	Black	19x5/3.5	500	5000	500	3	–	295	–
Aerial 8x5/3.5+2x10/8 Fig8 TIA MPB30225/8B	Black	8x5/ 3.5+2x10/ 8	500	5000	500	3	36 × 27	286	2000/K24, 1000/K20
Aerial 1x12/10 Fig8 TIA MPB30228/1B	Black	1x12/10	300	5000	500	3	25 × 14.5	150	1000/K12
Aerial 2x5/3.5+1x12/10 Fig8 TIA MPB30228/2B	Black	2x5/ 3.5+1x12/ 10	–	–	–	–	–	350	–
Aerial 5x5/3.5+4x12/10 Fig8 TIA MPB30228/5B	Black	5x5/ 3.5+4x12/ 10	500	5000	500	3	42 × 30.5	350	500/K16, 1000/K20
Aerial 8x5/3.5+2x12/10 Fig8 TIA MPB30228/8B	Black	8x5/ 3.5+2x12/ 10	550	5000	500	3	38 × 29	286	1000/K18
Aerial10x5/3.5+1x12/10 Fig8 TIA MPB30228/10B	Black	10x5/ 3.5+1x12/ 10	–	–	–	–	–	242	–
Aerial12x5/3.5+1x12/10 Fig8 TIA MPB30228/12B	Black	12x5/ 3.5+1x12/ 10	550	5000	500	3	40.5 × 21	259	2000/K22, 1000/K18

Article name	Color	Layout	Bend Radius [mm]	Tensile Force [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]	Length [m]
Aerial 26x5/3.5+1x12/10 Fig8 TIA MPB30228/26B	Black	26x5/ 3.5+1x12/10	-	-	-	-	-	400	-