



Microduct Assembly 20/16 mm

TWD 20/16 mm 2-4 -way S12

Features

- For direct burial
- 2 or 4 bundled ducts
- 20/16 mm microducts
- Low friction inner surface
- Longitudinal grooves for maximum installation lengths

Application

The thick walled microduct bundles consist of a number of microducts with an inner low friction surface that enables installation of air-blown fiber units or nano cables. The thick inner wall of the microducts allow for installation directly into the ground without the need for additional protection.

Design

The duct assemblies are available in several configurations from 2 to 4 microducts. 20/16 mm microducts are optimized for installation of micro cables and nano cables. The microducts have a low-friction inner surface with longitudinal grooves for best blowing performance.

Product Information

Microducts and outer sheath: HDPE

Technical Information

Color Code	S12
Temperature, Operation [°C]	-40 to +60
Temperature, Storage [°C]	-40 to +60
Temperature, Installation [°C]	-20 to +50
Conformance	<p>Abrasion: IEC 60794-1-2-E2B(1)</p> <p>Kink: IEC 60794-1-2-E10, 20 x outer diameter</p> <p>Impact: IEC 60794-1-2-E4</p> <p>Crush: IEC 60794-1-2-E3</p> <p>Tensile: IEC 60794-1-2-E</p> <p>Bend: IEC 60794-1-2-E11A</p> <p>Torsion: IEC 60794-1-2-E</p> <p>Flexibility: IEC 60794-1-2-E8</p> <p>Inner Clearance: IEC 60794-5-20, IEC 60794-5-10, Ann. D</p>
Marking	<p>Duct assemblies have markings showing the type and tube length. The individual microducts are identified by their colors (color stripes).</p> <p>12 different colors are used: according to the S12 standard.</p> <p>The assemblies are available in various sheath colors for easy identification.</p>

Technical Details

S12 Mikroörör 1-12 Microducts 1-12	1	2	3	4	5	6	7	8	9	10	11	12	
	Orange	Gul Yellow	Röd Red	Vit White	Grön Green	Violett Violet	Blå Blue	Grå Grey	Turkos Turquoise	Svart Black	Brun Brown	Rosa Pink	
	S12 Mikroörör 1-24 Microducts 1-24	1	2	3	4	5	6	7	8	9	10	11	12
		Orange 1	Gul 1 Yellow 1	Röd 1 Red 1	Vit 1 White 1	Grön 1 Green 1	Violett 1 Violet 1	Blå 1 Blue 2	Grå 1 Grey 1	Turkos 1 Turquoise 1	Svart 1 Black 1	Brun 1 Brown 1	Rosa 1 Pink 1
		13	14	15	16	17	18	19	20	21	22	23	24
		Orange 2	Gul 2 Yellow 2	Röd 2 Red 2	Vit 2 White 2	Grön 2 Green 2	Violett 2 Violet 2	Blå 2 Blue 2	Grå 2 Grey 2	Turkos 2 Turquoise 2	Svart 2 Black 2	Brun 2 Brown 2	Rosa 2 Pink 2

S12 Color Code Chart for Microduct Assemblies

Articles 5

Article name	Color	Layout	Bend Radius [mm]	Tensile Force, Installation [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]
Cable duct 2x20/16 S12 OG MPB30256/2M	Orange	2x20/16	440	3000	8000	15	42 × 22	318
Cable duct 2x20/16 S12 YE 4/MPB30256/2M	Yellow	2x20/16	440	3000	8000	15	42 × 22	318
Cable duct 2x20/16 S12 RD 2/MPB30256/2M	Red	2x20/16	440	3000	8000	15	42 × 22	318
Cable duct 2x20/16 S12 GN 1/MPB30256/2M	Green	2x20/16	440	3000	8000	15	42 × 22	318
Cable duct 4x20/16 S12 OG MPB30256/4M	Orange	4x20/16	840	5300	–	–	42 × 42	568