



Microduct Assembly 20/16 mm with Tracer

TWD 20/16 mm 1-7 -way Tr, TIA598 ft

Features

- For direct burial
- 1, 2, 4 or 7 bundled ducts
- 20/16 mm microducts
- Low friction inner surface

Application

The thick walled microduct are designed with an inner low friction surface that enables installation of micro cables or nano cables. The thick wall of the microducts allow for installation directly into the ground without the need for additional protection.

Design

The duct assemblies are available in several configurations from 1 to 7 microducts.
20/16 mm microducts are optimized for installation of micro cables and nano cables. The microducts have a low-friction innner surface with longitudinal grooves for best blowing performance.

Product Information

Microducts and outer sheath: HDPE

Technical Information

Color Code	TIA598
Temperature, Operation [°F]	-40 to 140 (-40 to +60°C)
Temperature, Storage [°F]	-40 to 140 (-40 to +60°C)
Temperature, Installation [°F]	-4 to +122 (-20 to +50°C)
Conformance	<p>Abrasion: IEC 60794-1-2-E2B(1)</p> <p>Kink: IEC 60794-1-2-E10, 20 x outer diameter</p> <p>Impact: IEC 60794-1-2-E4</p> <p>Crush: IEC 60794-1-2-E3</p> <p>Tensile: IEC 60794-1-2-E</p> <p>Bend: IEC 60794-1-2-E11A</p> <p>Torsion: IEC 60794-1-2-E</p> <p>Flexibility: IEC 60794-1-2-E8</p> <p>Inner Clearance: IEC 60794-5-20, IEC 60794-5-10, Ann. D</p>
Marking	<p>Duct assemblies have markings showing the type and tube length. The individual microducts are identified by their colors.</p> <p>12 different colors are used according to the TIA598 standard.</p> <p>The assemblies are available in various sheath colors for easy identification.</p>

Technical Details

TIA-598 Microducts 1-12	1	2	3	4	5	6	7	8	9	10	11	12
	Blue	Orange	Green	Brown	Slate	White	Red	Black	Yellow	Violet	Rose	Aqua
TIA-598 Microducts 1-24	1	2	3	4	5	6	7	8	9	10	11	12
	Blue 1	Orange 1	Green 1	Brown 1	Slate 1	White 1	Red 1	Black 1	Yellow 1	Violet 1	Rose 1	Aqua 1
	13	14	15	16	17	18	19	20	21	22	23	24
	Blue 2	Orange 2	Green 2	Brown 2	Slate 2	White 2	Red 2	Black 2	Yellow 2	Violet 2	Rose 2	Aqua 2

Articles 4

Article name	Color	Layout	Band Radius [in]		Tensile Force, Installation [lbs]	Dimensions [in]	Weight [lbs/100ft]
Microduct 1x20/16 Tr Orange ft MPB302571UV	Orange	1x20/16	8.4	315	0.84 (21.4mm)		101
Microduct 2x20/16 Tr Orange ft MPB302572UV	Orange	2x20/16	8.7	674	0.87x1.65 (22x42mm)		212
Microduct 4x20/16 Tr Orange ft MPB302574UV	Orange	4x20/16	16.5	1190	1.65x1.65 (42x42mm)		382
Microduct 7x20/16 Tr Orange ft MPB302577UV	Orange	7x20/16	20	1980	2.23x2.44 (56.6x62.0mm)		630