



ODF – The NCD513 Series

Optical Distribution Frame - 1.5U

Funktioner

- 1.5U for 19" or ETSI mount
- Small depth 250 mm (within ETSI)
- Up to 48 fibers (using 24 x SC duplex cut out slots)
- Front serviced
- Supports SC, FC, ST and LC adapters

Applicering

The 1.5 U high unit is used for small to medium number of terminations. The unit is typically used for sites where the incoming cable (up to 48 fibers) allows to be terminated directly in the ODF. The ODF supports a wide selection of connector and incoming cable options.

Design

The unit is suitable for the installation of pigtails or pre-terminated cables. An installation kit with all the necessary holders for splice protection sleeves, strain relief holders, etc is available (not included).

A horizontal patch guide (0.5 U) to be mounted underneath the ODF is available as an optional accessory.

The termination unit comprises a chassis, a drawer with front panel, a combined cable entrance/strain relief, two angled mounting brackets and a cover. All done in a modular way for front serviced time saving installations and maintenance.

The mounting brackets fit the chassis in three different locations for various mounting depth.

By turning the brackets the unit will fit either 19" or ETSI rack.

The brackets also permit wall mounting.

The optical performance of the ODF connections used in the Hexatronic systems is ensuring the right quality and stability over time.

Produktinformation

The termination unit is made of painted Aluzinc sheet steel. All products are in accordance with RoHS.

Teknisk information

Produktfärg	Coral white
Tekniska noteringar	The termination unit can be fitted with cable entrances for up to 4 cables with maximum outer diameter of 20 mm, two from each side, located at the rear.
Beställningsinformation	Adaptors are not included. "Blind plugs" are available to cover empty adapter slots in case of adaptation to lower numbers of connections.

Artiklar

Artikelnamn	E-Nr.	Färg	Antal fibrer	Upplägg	Dimensioner [mm]	Vikt [kg]
ODF 1.5U 12 SC-DUPLEX NCD5130211	5010022	Vit	–	12xSCDupl	440 × 247 × 66	3.49
ODF 1.5U 18 SC-DUPLEX NCD5130212	5055430	Vit	–	18xSCDupl	440 × 247 × 66	3.68
ODF 1.5U 24 SC-DUPLEX NCD5130213	5010023	Vit	–	24xSCDupl	440 × 247 × 66	3.49
ODF 1.5U 24 LC-QUAD NCD5130213/96LC		Vit	96	96xLC	440 × 247 × 66	3.49
ODF 1.5U 24 FC NCD5130303	5010025	Vit	24	24xFC	440 × 247 × 66	3
Installation kit for ODF NTM50383	5055407	–	–	–	–	0.108
Horizontal cable guide NTM504036	5055408	–	–	–	–	0.33
Cable guide, horizontal for 19"-rack 02/NCD513	5084196	Vit	–	–	–	0.4