



Duct Joint Closure

Heat Shrink

Features

- Straight joint for tight protected microduct assemblies
- Heat shrink for maximum protection
- Sizes for 1 - 24 microducts

Application

This jointing kit for 5/3.5 and 10/8 mm microduct assemblies are intended for outdoor splicing of straight joints, using the well approved heat shrink method.

The kit is suitable for direct buried applications such as normal service joints.

Design

The kit consists of aluminium foil as moisture barrier, duct connectors, tube for mechanical protection, graining cloth for cleaning and heat shrink tube. The joints are designed to enable continuity of the duct foil for grounding purposes.

Technical Information

IP Rating

IP68

Articles 6

Article name	Weight [kg]	Length [m]
STRAIGHT JOINT 1X5MM RIBBONET, OUTD NDE45115/1	0.08	300
STRAIGHT JOINT 2-7X5MM RIBBONET, OU NDE45115/2	0.23	400
STRAIGHT JOINT12-24X5MM RIBBONET,OU NDE45115/3	0.52	750
STRAIGHT JOINT 1X10MM MICRONET, OUT NDE45115/4	0.145	–
STRAIGHT JOINT 4X10MM MICRONET, OUT NDE45115/5	0.232	–
STRAIGHT JOINT 7X10MM MICRONET, OUT NDE45115/6	0.405	–