

# **Customer Wall Box**

Up to 6 Terminated Drops

#### Features

- Very appealing and compact design
- High capacity with up to six LC/APC connectors and 12x ANT splices
- Delivered complete with adapters, pigtails and ANT crimp protectors for super-fast installation
- Input microduct or cable up to 10mm diameter
- Approved according to the Material Concept of The Federal German Government
- IP 44 rated.

# **:**exatronic

## Application

The customer wall box is as a very compact, yet installer friendly, termination point indoors for FTTH networks or similar

with 2, 4 or 6 fibers. The product is particularly well suited for standard microduct dimensions such as 7mm or 10mm. The six

fiber version is approved according to the Material Concept of the Federal German Government. To save installation time, simplify logistics and ordering, the customer wall box is delivered as a complete kit with adapters

and pigtails already fitted and all other required accessories included in one box.

### Design

The box is made of a robust plastic material with a metal mounting plate made of metal. The metal mounting plate can be mounted directly on the wall. The cover is attached to the base with two torx screws hidden under a logo plate in the center of the cover.

Three holders for adapters are installed in the base which gives a capacity of three SC or three LCduplex adapters. The adapter ports are labelled from 1 - 6 on the cover. Depending on configuration the unused ports are closed with break out covers.

The 6-f version is approved according to the Material Concept of the Federal German Government. UV rated polymer used.

### **Technical Information**

IP Rating	44
Ordering Information	All versions of the box are supplied complete with adapters,
	pigtails and ANT crimp protectors as well as accessories
	such as grommets, cable ties and screws.
	Recommended accessories are the MPB30608 divisible
	seals.

#### Articles 4

