

Customer Wall Box

Up to 12 Terminated Drops

Features

- Very compact design
- High capacity with up to 12 LC/APC connectors and 12x ANT splices
- Delivered complete with adapters, pigtails and ANT crimp protectors for super-fast installation
- Very flexible sealing sets for input microduct up to 12mm diameter and multiple output choices
- Approved according to the Material Concept of the Federal German Government
- IP 54 rated



Application

The customer wall box is as a very compact, yet installer friendly, internal or external termination point for FTTH

networks or similar with up to 12 fibers. The product is particularly well suited for air-blown concepts and standard microduct dimensions such as 7, 10 or 12mm. The product is approved according to the Material Concept of the Federal German Government for dual homes (10F is minimum).

To save installation time, simplify logistics and ordering, the customer wall box is delivered as a complete kit with adapters and pigtails already fitted and all other required accessories included in one box.

Design

The box is made of a robust plastic material with UV stable properties. The cover is hinged at the top and is secured to the base with a lock.

Six holders for adapters are installed in the base which gives a capacity of six SC or six LC-duplex adapters.

In the lower area three inlet and outlet ports are implemented, which are delivered closed and can then be loaded with the needed pre-perforated seal sets (rubber grommets). The following seal sets are included: $1x \varnothing 10$ mm, $2x \varnothing 7$ mm, $1x 2x \varnothing 7$ mm, $1x 12x \varnothing 5$ mm and 1x 24x up to $\varnothing 3$ mm. It is also possible to install a PLC splitter in a special clip (included) in the bottom plate. UV rated polymer used.

Technical Information

ID Detine	IDE 4
IP Rating	IP54

pigtails and ANT crimp protectors as well as accessories

such as grommets, cable ties and screws.

Recommended accessories are the MPB30608 divisible

seals.



Articles 3

		·	fibers t	thressions throi
Article name	color	₩.	thers Layout	Time II.
FTTH wall outlet 12f NEG206101	White	12	_	120 × 105 × 22.8
FTTHwall outlet 10f NEG206101/10	White	10	bestückt mit Kupplung und Rgtails (10xLC/APC)	120 × 105 × 22.8
FTTH wall outlet 12f NEG206101/12	White	12	bestückt mit Kupplung und Rgtails (12xLC/APC)	120 × 105 × 22.8