



# Ribbon fanout G652.D

**Ribbon fanout 2 to 12 fibers and connectors mounted at one end. Built with transparent protective tube.**

---

## Design

Protecting tube:

**Single fiber:** 80 cm

**Ribbon:** 150 cm

## Product Information

Each separate fanout is marked with a unique ID number for full traceability.

We supply fanouts with all contact devices available on the market. The material in the contact housing is plastic or metal, the ferule is made of zirconia.

## Technical Information

**TECHNICAL INFORMATION**

<b>Temperature, Operation [°C]</b>	-20 °C to +75 °C
<b>Temperature, Storage [°C]</b>	-20 °C to +75 °C
<b>Fiber Type</b>	G652D
<b>Insertion Loss, max [dB]</b>	≥ 0.12
<b>Return Loss, min [dB]</b>	≥55 UPC / ≥65 APC

**Technical Notes**

Each individual fanout is equipped with dust cover on the connectors and packed in a sealed plastic bag. The label indicates all connector attenuation (IL) and reflection (RL).

**Radie (2,5 mm):** 10-25 mm (UPC) 5-12 mm (APC)

**Radie (1,25 mm):** 7-20 mm (UPC) 5-12 mm (APC)

**Apex offset:** ≤50 µm

**Angle offset:** 0,2° (UPC) 0,3° (APC)

## Articles 8

Article name	No. of Fibers	Layout	Length [m]	Form of Delivery
Fanout 4xSM G652D f1&3 SC/UPC f2&4 SC/APC 2,3m 440Y01	4	SC&SCA	2.3	Plastic bag
Fanout 4xSM G652D LC/APC 2,3m 440N01	4	LCA	2.3	Plastic bag
Fanout 4xSM G652D LC/UPC 2,3m 440L01	4	LC	2.3	Plastic bag
Fanout 4xSM G652D SC/APC 2,3m 440601	4	–	2.3	Plastic bag
Fanout 4xSM G652D SC/UPC 2,3m 440401	4	SC	2.3	Plastic bag
Fanout 8xSM G652D LC/UPC 2,3m 480L01	8	LC	2.3	Plastic bag
Fanout 8xSM G652D SC/APC 2,3m 480601	8	SCA	2.3	Plastic bag
Fanout 8xSM G652D SC/UPC 2,3m 480401	8	SC	2.3	Plastic bag