



Ribbon fanout G657A

Ribbon fanout 2 to 12 fibers and connectors mounted at one end. Built with transparent protective tube.

Design

Protecting tube:

Single fiber: 80 cm

Ribbon: 150 cm

Product Information

Each separate fanout is marked with a unique ID number for full traceability.

We supply fanouts with all contact devices available on the market. The material in the contact housing is plastic or metal, the ferule is made of zirconia.

Technical Information

TECHNICAL INFORMATION

Temperature, Operation [°C] -20 °C to +75 °C

Temperature, Storage [°C] -20 °C to +75 °C

Insertion Loss, max [dB] ≥ 0.12

Return Loss, min [dB] ≥ 55 UPC / ≥ 65 APC

Technical Notes Each individual fanout is equipped with dust cover on the connectors and packed in a sealed plastic bag. The label indicates all connector attenuation (IL) and reflection (RL).

Radie (2,5 mm): 10-25 mm (UPC) 5-12 mm (APC)

Radie (1,25 mm): 7-20 mm (UPC) 5-12 mm (APC)

Apex offset: ≤ 50 μm

Angle offset: 0,2° (UPC) 0,3° (APC)

Articles 6

Article name	Color	No. of Fibers	Layout	Length [m]	Form of Delivery
Fanout 2xSM G657A SC/APC 2,3m A20601	–	2	SCA	2.3	Plastic bag
Fanout 4xSM G657A SC/UPC 2,3m A40401	Blue	4	SC	2.3	Plastic bag
Fanout 4xSM G657A SC/APC 2,3m A40601	Blue	4	SCA	2.3	Plastic bag
Fanout 4xSM G657A LC/UPC 2,8m (1,3m+1,5m) A40L01	Blue	4	LC	2.8	Plastic bag
Fanout 4xSM G657A LC/APC 2,3m A40N01	Blue	4	LCA	2.3	Plastic bag
Fanout 8xSM G657A SC/APC 2,3m A80601	Blue	8	SCA	2.3	Plastic bag