



Ribbon fanout Multimode

Ribbon fanout 4 fibers and connectors mounted at one end. Built with transparent protective tube.

Design

Protecting tube:

Single fiber: 80 cm

Ribbon: 150 cm

Product Information

Each separate fanout is marked with a unique ID number for full traceability.

We supply fanouts with all contact devices available on the market. The material in the contact housing is plastic or metal, the ferule is made of zirconia.

Technical Information

Technical Information

Temperature, Operation [°C] -20 °C to +75 °C

Temperature, Storage [°C] -20 °C to +75 °C

Insertion Loss, max [dB] ≥ 0.2

Technical Notes Each individual fanout is equipped with dust cover on the connectors and packed in a sealed plastic bag. The label indicates all connector attenuation (IL) and reflection (RL).

Radie (2,5 mm): 10-25 mm

Radie (1,25 mm): 7-20 mm

Apex offset: $\leq 50 \mu\text{m}$

Angle offset: 0,3°

Articles 2

Article name	Nb. of Fibers	Length [m]	Form of Delivery
Fanout 4x62,5/125 OM1 SC/PC 2,3m 540401	4	2.3	Plastic bag
Fanout 4x50/125 OM2 SC/PC 2,3m 640401	4	2.3	Plastic bag