



Multi Power Cable for FTTA Applications

RQAFQ 5 x 2 x 10 mm²


Features

- Jacket of weather proof and fire retardant material
- For outdoor and indoor applications
- Flexible cable with down to 6xD bend radius
- Common screen of Al tape for easy grounding with clamps
- Cable size 10 mm²
- Drain wire 2 x 10 mm²
- Color coded and number marked power cords
- Flame retardant EN 50575 B2ca - s1, d0
- ROHS compliant

Application

A robust and compact power distribution cable for interconnecting power between main and remote units for outdoor and indoor radio base stations.

Product Information



- 1 Power cable unit conductor: Stranded tin-plated copper wire class 5
- 2 Insulation: Flame retardant colored halogen-free thermoplastic compound
- 3 Drain wire: Stranded tin-plated copper wire 2x10 mm²
- 4 Screen: Aluminum tape
- 5 Ripcord: Aramid yarn
- 6 Jacket: Flame retardant halogen-free thermoplastic compound

Technical Information

Tuotteen väri	Black
Lämpötila, käyttö [°C]	-40 to +80
Palo-ominaisuudet	EN 50575 B2ca - s1, d0
Jänniteluokka [V]	100
Vaatimustenmukaisuus	Flame resistance according to EN 50575 B2ca - s1, d0
Merkintä	Manufacturer, year and week of manufacture, product No., and length marking
Tilautiedot	Supplied lengths: On request

Articles 1

Article name	Halkaisija Ø [mm]	Paino [kg/km]
RQAFQ 5x2x10mm2 +2x10mm2 TFL700040	26	1360