

VIPER™



High Performance Micro Cable – Aerial Applications

GNHL 12-96 fibers G657A1 S12

Features

- Optimized for aerial duct installation
- Excellent installation performance
- Bend resistant G657A1 fibers
- Unique design with robust inner tubes that do not kink
- Temperature range from -40 to +70°C
- Easy to prepare and identify fibers
- Slim design for microducts down to 8mm
- Halogen-free
- Up to 96 fibers

Application

The aerial micro cable is a cable for installation into microducts mounted on pole lines (aerial installation). The cable is part of the Hexatronic Micro Cable System. The system is used for installing optical fibers in all types of metropolitan and rural access networks. The system provides an easy, cost-efficient rollout and maintenance, which creates the opportunity for increasing broadband penetration, with the capability to grow with user needs.

Design


The Micro Cables are designed with inner protective tubes made of a unique compound. The Polyamide gives a special strength to the product, while increasing the bending properties as well as other benefits such as extreme temperature resistance.

As a result, Hexatronic Micro Cables are more durable during the installation process as they are able to withstand rough handling.

The unique cable design with an extended operational temperature range of -40 to +70°C can be used in many environments, on all continents where heat and cold are often a factor.

The micro cable consists of up to 8 loose tubes with 12 fibers per tubes. This enables a fiber count from 12 to 96 fibers.

Product Information



- 1 Primary coated fiber: Silica, acrylate
- 2 Loose tube: PA
- 3 Central strength member: Glass fiber reinforced plastic, PE
- 4 Slit up yarn: Aramide yarn
- 5 Wrapping: Water blocking yarns
- 6 Sheath: Polyethylene, halogen-free

Black fillers can replace empty white tubes.

Technical Information

| | |
|--------------------------------|---|
| Product Color | Black Sheath |
| Color Code | S12 |
| Temperature, Operation [°C] | -40 to +70 |
| Temperature, Storage [°C] | 40 to +70 |
| Temperature, Installation [°C] | -15 to +50 |
| Water Blocking | Longitudinal water blocking according to IEC 60794-1-2-F5C |
| Fiber Type | G657A1 |
| Attenuation @Wavelength [nm] | 1310/1383/1550 |
| Typical Attenuation [dB/km] | 0.32/0.32/0.18 |
| Average Attenuation [dB/km] | 0.33/0.33/0.21 |
| Maximum Attenuation [dB/km] | 0.36/0.36/0.23 |
| Conformance | Longitudinal water blocking according to IEC 60794-1-2-F5C. Mechanical and environmental tests in accordance with IEC 60794-5-10. Fiber parameters and tests according to the IEC series 60793-2 and 60793-1. |
| Marking | Example of sheath marking, 1 time/meter: "HEXATRONIC A35 Viper Aerial yymmddhh TOL4019029/96AH GNHL-U-CDGNRV 96/T12 G657A1 S12 xxxx M" where yymmddhh = year, month, day and hour of manufacture, xxxx=running meter marking. |

Installation Notes

Typical installation performance:

- Ducts ID 8-10 mm, cable OD ≤6.7 mm: 2000 m

Installation performance verified on Hexatronic test track, according to IEC 60794. Installation performance is affected by the installed path, environmental conditions, installation equipment etc and actual performance may therefore deviate from the above specified values.

The cable should be installed at a temperature between -15 to +40°C. The cable shall not be stored in direct sunlight.

The sun may heat up the cable over the permitted temperature limit.

Ordering Information

Supplied lengths: 2, 4, 8 km

Technical Details

| | | | | | | | | | | | | |
|---|------------|-------------|--------------|---------------|---------------|-------------|---------------|----------------|-------------------|--------|---------------------|--------------|
| S12 Fibers och rör Fibers and tubes | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| | Röd Red | Blå Blue | Vit White | Grön Green | Gul Yellow | Grå Grey | Brun Brown | Svart Black | Violett Violet | Orange | Turkos Turquoise | Rosa Pink |
| | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 |
| | Röd Red | Blå Blue | Vit White | Grön Green | Gul Yellow | Grå Grey | Brun Brown | Klar Clear | Violett Violet | Orange | Turkos Turquoise | Rosa Pink |

Articles 5

| Article name | Color | No. of Fibers | Layout | Bend Radius [mm] | Tensile Force [N] | Crush [N/100 mm] | Diameter Ø [mm] | Weight [kg/km] | Length [m] |
|--|-------|---------------|--------|------------------|-------------------|------------------|-----------------|----------------|-----------------------|
| GNHL 12/T12 G657A1 S12 Aerial TOL4019029/12AH | Black | 12 | 1x12 | 23 | 700 | 2000 | 5.7 | 28 | 8000/K10, 4000/K8 |
| GNHL 24/T12 G657A1 S12 Aerial TOL4019029/24AH | Black | 24 | 2x12 | 23 | 700 | 2000 | 5.7 | 28 | 8000/K10, 4000/K8 |
| GNHL 48/T12 G657A1 S12 Aerial TOL4019029/48AH | Black | 48 | 4x12 | 23 | 700 | 2000 | 5.7 | 28 | 8000/K10, 4000/K8 |
| GNHL 72/T12 G657A1 S12 Aerial TOL4019029/72AH | Black | 72 | 6x12 | 23 | 700 | 2000 | 5.7 | 28 | 8000/K10, 4000/K8 |
| GNHL 96/T12 G657A1 S12 Aerial TOL4019029/96AH | Black | 96 | 8x12 | 23 | 700 | 2000 | 6.7 | 39 | 4000/K10, 8000/K12 |